

GENERON MARINE N₂ GENERATING SYSTEMS

MEMBRANE Cabinet Series

- Cargo Hold and Hull Fumigation
- Cargo Hold Inerting / Oxidation Control
- FPSO (Floating Production, Storage & Offloading Systems)
- Inerting of Flammable Liquids
- LNG / LPG
- Purging
- Transporting Perishable Goods



For over 40 years **GENERON** has been the world leader in the design and manufacture of Nitrogen Generators. **GENERON**[®] has supplied thousands of Nitrogen Generators, from cabinet to large containerized systems, around the world. These systems are energy efficient, have a 30% smaller footprint and are low maintenance. Our maintenance and parts programs ensure your systems long term efficient operation.

The **GENERON**[®] Marine Cabinet Series is ideal where low to medium Nitrogen flow rates are required in a small footprint. **GENERON**[®] Marine Series is designed and manufactured using the patented **GENERON**[®] Hollow Fiber Membranes. These highly engineered systems produce high flow rates in a range of cabinet designs and sizes. From our 4000 series to our dual stainless series and retrofits, **GENERON** delivers a superior product and customer service.

Our ISO 9000, ASME, PED, UL/CSA and GOST certified facilities and shops in Texas and California ensure the highest-standards are met and your expectations exceeded.

FEATURES & BENEFITS

- **Convenient:** Fully Automatic Unattended Operation
- **Easy:** Maintenance and operation
- **Economical:** Low Operating Cost
- **Reliable:** Systems Built to Last
- **Safe:** Low Operating Pressures, no Hazardous Storage
- Hydrocarbon free
- Nitrogen Dew Point down to -70°F (57°C)
- Nitrogen purities up to 99.999%
- Optional Dew Point feature of -100°F (-73°C)
- Oxygen Analyzer
- PLC



MARINE N₂ MEMBRANE SYSTEMS

Cabinet Series

NITROGEN OUTPUT FLOW RATE—4000 Series Cabinets				
	4001		4002	
Pressure PSIG / BAR G	Nitrogen Flow SCFM / Nm3/hr	Air Demand SCFM / Nm3/hr	Nitrogen Flow SCFM / Nm3/hr	Air Demand SCFM / Nm3/hr
100 / 6.9	11 / 17	23 / 37	21 / 34	47 / 74
150 / 10.3	19 / 30	40 / 62	38 / 60	76 / 120
175 / 12.0	23 / 36	46 / 73	46 / 72	92 / 144

NITROGEN OUTPUT FLOW RATE—6000 Single & Dual Cabinets All flow rates are rated at 95% Purity				
	6001-4		6005-8	
Pressure PSIG / BAR G	Nitrogen Flow SCFM / Nm3/hr	Air Demand SCFM / Nm3/hr	Nitrogen Flow SCFM / Nm3/hr	Air Demand SCFM / Nm3/hr
100 / 6.9	140 / 220	312 / 490	280 / 440	625 / 980
150 / 10.3	254 / 400	535 / 840	510 / 800	1070 / 1680
175 / 12.0	303 / 477	630 / 990	607 / 954	1261 / 1980

**Flow rates at standard atmospheric conditions (77°F and 14.7 psi.)

***Dew point at < -85°F **Additional purities and flows available.**

Approximate Weight and Dimensions				
Size	L inch / mm	W inch / mm	H Inch / mm	Weight lbs. / kg
4000 Series	30 / 762	28 / 711	66 / 1676	250 / 112
6000 Series	32 / 812	32 / 812	90 / 2286	800 / 360
6000 Dual	64 / 1625	32 / 812	90 / 2286	1200 / 540



GENERON

16250 Tomball Parkway
Houston, Texas 77086
O - +1 .713. 937.5200
F - +1 .713. 937.5250
www.generon.com

GENERON



D-Marine-SeriesLP-0617